

PM-50Vet

Pulse Oximeter

Technical Specifications

Description

The PM-50 pulse oximeter is intended for noninvasive spot-check measurement of functional oxygen saturation of arterial hemoglobin (SpO₂).

SpO₂

Range 0-100%
Resolution 1%
Accuracy (70-100%) ±2% Adult
±3% Neonate
unspecified (0%-69%)
Method Dual wavelength LED

Heart (Pulse) Rate

Range 25-254bpm
Resolution 1bpm
Accuracy ±2bpm

Display

Type Backlit LCD
Parameters SpO₂; PR; Pleth. bar
Status Standby; Communication; Download
Information Patient ID; Indicator of data storage; Low power; Error

Mechanical

Weight 130g without batteries
Size 140 x 65 x 31 mm

Battery

Type 4 AA Alkaline batteries or 4 AA rechargeable batteries
Life Approximately 15 hours for normal measurement status

Environmental

Operating Temperature 0 - 50°C
Storage Temperature -20 - 60°C
Operating Humidity 15%RH - 95%RH
Storage Humidity 10%RH - 95%RH

Classification

Type of Protection Internally powered equipment
Degree of Protection BF
Safety IEC 60601-1, EN 865, ISO 14971

Storage

Patient ID Up to 100
Data records Up to 200

System Output

Com Port RS-232
Auxiliary Software Record management and data Printing through PC



Mindray Co., Ltd.

Headquarters: Mindray Building, Keji 12th Road South, High-tech Industrial Park, Nanshan, Shenzhen 518057, P. R. China

Tel: +86 755 26582484, 26582888 Fax: +86 755 26582500, 26582501

E-mail: vet-market@mindray.com.cn Website: www.mindray.com.cn



North America Office:
4885 Kingsway, Suite 311 Burnaby, B.C., V5H 4T2, Canada
Toll free: 800-656-9088 Tel: +1 604-451-1199 Fax: +1 604-451-1189